



TECH DATA SHEET

(optional) ACCENT PAINT

STEPS for U Do It Coatings' Concrete Stain System:

Degreaser & Stain Treatment (optional - mostly garages)

1 - Eco Prep & Clean (clean/etch concrete)

Patch Kit (optional - to patch concrete)

2 - Decorative Concrete Stain (use one or multiple colors)

Accent Paint (optional - create borders or designs)

3 - Clear Acrylic Sealer (seal concrete)

Protective Wax (suggested to maintain interiors floors)

Maintain Clean (best maintenance cleanser for interiors)

DESCRIPTION AND USE: U Do It Coatings' **Accent Paint** is used to create borders and/or designs on the newly stained concrete surface before sealing. This water-based, pigmented, 100% acrylic paint/sealer is very easy to use. It is UV stable, meaning that it is safe to use for interior and exterior applications, since it will not discolor in direct sunlight. Do not apply directly to bare concrete. The concrete must be stained first, since U Do It Coatings' **Decorative Concrete Stain** acts as a primer.

COLORS/SIZE: Available in Pints (16 oz.) Seven Standard Colors: Black, Brick, Canyon, Cocoa, Espresso, Gray and Sand.

COVERAGE RATE: Pint covers approx. 100 linear ft. (4" width, two coats.) Coverage rates vary, depending on application technique, applicator, weather conditions, surface texture and porosity.

APPLICATION TEMPERATURES: Substrate temperature MUST be between 50-100° F. Ambient temperatures should be at least 60°F and rising. Do not apply to surface temperatures under 50°F since this water-based product can freeze. Do not allow product to freeze during shipping or storage.

APPLICATION: Apply two thin coats with brush or small, low-nap (1/2") roller cover. Do not apply too thick. Let first coat dry completely before applying second. Dry times vary

with thickness, temperature, humidity, and other conditions. An average dry time is two hours.

It is not advisable to use tape to create borders, since tape can pull up newly applied stain. If using tape or templates, let the stain cure AT LEAST 72 hours and gently test. Instead, we suggest drawing lines and designs free hand. Carefully measure out from the wall, draw the line with a pencil, and paint in the **Accent Paint** border free hand. Be aware that not all walls or concrete slabs are perfectly square, so "cheat" lines for a better appearance, if necessary.

Once the second coat of **Accent Paint** is dry to the touch and not tacky to walk on, apply **Clear Acrylic Sealer**.

This is an industrial-quality product – USE AT OWN RISK. Follow all directions carefully. Keep out of the reach of children. Thoroughly read this Tech Data Sheet, "Instructions for Staining Interior (or Exterior/Garage) Concrete Floors," label on container, and SDS (Safety Data Sheet) before using. Watch all How-To Videos on our website and email us at questions@uDoItCoatings.com.

CLEAN UP: Water and mild soap.

AFTER APPLICATION: Your completed project should not be exposed to water for at least 48 hours so that products can fully cure. See sealer Tech Sheet for more curing details.

DISPOSAL: Re-seal partially used containers after use. Dispose of unused material per local, state and federal regulations.

WARNING: Harmful if swallowed. Avoid contact with eyes and skin. Goggles and gloves are recommended. Avoid breathing mist or vapors. Use with adequate ventilation. Refer to SDS (Safety Data Sheet) for more info.

HANDLING PRECAUTIONS: Avoid contact with skin. Wear safety glasses and protective gloves. Refer to SDS (Safety Data Sheet) for the most complete info.

FIRST AID: INGESTION: Obtain medical attention at once. EYE CONTACT: Flush with clean water for 15 minutes and obtain medical attention. INHALATION: Remove to fresh air and obtain medical attention. SKIN CONTACT: Wash with soap and water. Obtain medical attention if irritation is severe or persistent. Refer to SDS (Safety Data Sheet) for the most complete info.

MOISTURE VAPOR/ ALKALINITY PRECAUTIONS: All interior concrete floors not poured over an effective moisture vapor retarder/system are subject to possible moisture vapor transmission and related high levels of alkalinity that may lead to efflorescence, blistering and complete failure of the stain and sealer. It is the homeowner/applicator's responsibility to know the condition of the substrate. If necessary, conduct calcium chloride and relative humidity probe testing to determine if excessive levels

of vapor emissions or alkalinity are present before applying any coating. *U Do It Coatings* and its employees will not be responsible for coating failures due to undetected moisture vapor emissions or related high levels of alkalinity.

WARRANTY INFORMATION: If there is a coating failure, such as flaking, peeling, or chipping, it is almost always caused by faulty/inferior concrete, incomplete surface preparation, and/or incorrect application technique. If you reviewed and followed ALL of the instructional information, contact us to fill out a Complaint Form. Also provide a *U Do It Coatings*' receipt and ALL batch numbers. We will not accept partially filled out Complaint Forms or for projects over one year old. These Forms will be investigated by *U Do It Coatings* with the cooperation of the contractor/homeowner who installed the products. *U Do It Coatings* will not under any circumstance be liable for damages in excess of the purchase price of the products used on the project. *U Do It Coatings* is not liable for consequential or secondary damages resulting from the failure of a warranted item or the failure to provide services due to conditions beyond its control.

LIMITATIONS ARE DAMAGES CAUSED BY: 1. The customer due to neglect, abuse, or lack of reasonable care. 2. Settling due to expansive soil, fill dirt movement, drainage, alkali-silica reaction, or efflorescence. 3. Acts of God. 4. Improper installation.

DISCLAIMER AND LIMITATION OF LIABILITY:

To the best of our knowledge, the information contained herein is accurate. The warranty described herein shall be in lieu of any other warranty, expressed or implied, including but not limited to, any implied warranty of merchantability or fitness for a particular purpose. There are no warranties that extend beyond the description on the face hereof. The Buyer's sole and exclusive remedy against the Seller shall be for the replacement of the products or refund of the purchase price in the event that a defective condition of the products should be found to exist. No other remedy (including, but not limited to, incidental or consequential damages for lost profits, lost sales, injury to person or property, or any other incidental or consequential loss) shall be available to the Buyer. The sole purpose of this exclusive remedy shall be to provide Buyer with replacement of the products or refund of the purchase price of the products if any defect in materials or workmanship is found to exist. The exclusive remedy shall not be deemed to have failed its essential purpose so long as the Seller is willing and able to replace the defective products or refund the purchase price. The Buyer must give the Seller notice in writing of any alleged defect covered by this warranty together with all identifying details, including the Product Code(s), description and date of purchase, within thirty (30) days of the discovery of the defect. Final determination of the suitability of the material for the use contemplated, the manner of use, and whether the use infringes any patents, is the sole responsibility of the Buyer.