



# TECH DATA SHEET

(optional)

## DEGREASER & STAIN TREATMENT

### STEPS for U Do It Coatings' Concrete Stain System:

**Degreaser & Stain Treatment** (optional - mostly garages)

**1 - Eco Prep & Clean** (clean/etch concrete)

**Patch Kit** (optional - to patch concrete)

**2 - Decorative Concrete Stain** (use one or multiple colors)

**Accent Paint** (optional - create borders or designs)

**3 - Clear Acrylic Sealer** (seal concrete)

**Protective Wax** (suggested to maintain interiors floors)

**Maintain Clean** (best maintenance cleanser for interiors)

**DESCRIPTION AND USE:** U Do It Coatings' **Degreaser & Stain Treatment** is an industrial strength cleanser that aggressively breaks down oil, grease, tar, rust, and other stubborn stains from concrete and sealed surfaces.

This product is used mostly on exteriors such as driveways, garages, and BBQ areas. After problem areas have been treated, follow with U Do It Coatings' **Eco Prep & Clean** to fully clean and etch concrete (if staining concrete.) For interior floors, **Eco Prep & Clean** is typically the only product needed to prepare concrete for stain.

**AVAILABLE IN:** One-gallon containers only. Larger sizes are not cheaper and are harder to use and ship.

**COVERAGE RATE:** Full-strength stain treatment - approx. 300 sq. ft. per gallon. For diluted applications - use approx. 1 gallon to every 3 gallons of water for approx. 500 sq. ft.

**APPLICATION TEMPERATURES:** The optimal concrete temperature range for applying entire stain system is between 50-100° F. Do not allow product to freeze during shipping or storage.

**APPLICATION: For Exteriors/Garage Floors:** Pressure wash area and let dry to assess overall condition of concrete to be stained. If concrete has tar, grease, or other stubborn stains, scrape (if needed) and mist with water. Pour undiluted

**Degreaser & Stain Treatment** directly on problem area. Aggressively brush and let work for several minutes before rinsing away. Repeat if necessary. If stains deeply penetrated concrete, realize that dark spots could still be visible, even after several degreasing treatments. Typically, it is fine to proceed. Realize that camouflaging stains with a mottled effect may be necessary.

**For Interior Floors:** Mask off walls and other areas, if needed, with plenty of paper, plastic and tape. If concrete has stubborn stains, scrape and lightly mist with water. Pour undiluted **Degreaser & Stain Treatment** directly on problem area. Aggressively brush and let work for several minutes. Rinse away with a fine mist attachment on hose until water runs clear WHILE using wet/dry vacuum. Do not allow solution to puddle.

**General Use:** This product can also be used on concrete as a good maintenance cleanser/degreaser for exteriors. Pour on surface, let it set for a few minutes, aggressively brush, and rinse with high pressure nozzle or pressure washer until water runs clear.

This is an industrial-quality product – USE AT OWN RISK. Follow all directions carefully. Keep out of the reach of children. Thoroughly read this Tech Data Sheet, “Instructions for Staining Interior (or Exterior/Garage) Concrete Floors,” label on container, and SDS (Safety Data Sheet) before using. Watch all How-To Videos on our website and email us, if needed, at [questions@UDoItCoatings.com](mailto:questions@UDoItCoatings.com).

**CLEAN UP:** Water and mild soap.

**DISPOSAL:** Re-seal partially used containers after use. Dispose of unwanted material per local, state and federal regulations.

**WARNING:** Harmful if swallowed. Avoid contact with eyes and skin. Goggles and gloves are recommended. Avoid breathing mist or vapors. Use with adequate ventilation. Use a MSHA/NIOSH approved cartridge-type respirator if desired/necessary. Refer to SDS (Safety Data Sheet) for the most complete information.

**HANDLING PRECAUTIONS:** Avoid contact with skin. Wear safety glasses and protective gloves. Refer to SDS (Safety Data Sheet) for the most complete information.

**FIRST AID:** INGESTION: Obtain medical attention at once. EYE CONTACT: Flush with clean water for 15 minutes and obtain medical attention. INHALATION: Remove to fresh air and obtain medical attention. SKIN CONTACT: Wash with soap and water. Obtain medical attention if irritation is severe or persistent. Refer SDS (Safety Data Sheet) for the most complete information.

**WARRANTY INFORMATION:** If there is a coating failure, such as flaking, peeling, or chipping, it is almost always caused by faulty/inferior concrete, incomplete surface preparation, and/or incorrect application technique. If you reviewed and followed ALL the instructional information, contact us to fill out a Complaint Form. Also provide a *U Do It Coatings*' receipt and ALL batch numbers. We will not accept partially filled out Complaint Forms or for projects over one year old. These Forms will be investigated by *U Do It Coatings* with the cooperation of the contractor/homeowner who installed the products. *U Do It Coatings* will not under any circumstance be liable for damages in excess of the purchase price of the products used on the project. *U Do It Coatings* is not liable for consequential or secondary damages resulting from the failure of a warranted item or the failure to provide services due to conditions beyond its control.

**LIMITATIONS ARE DAMAGES CAUSED BY:** 1. The customer due to neglect, abuse, or lack of reasonable care. 2. Settling due to expansive soil, fill dirt movement, drainage, alkali-silica reaction, or efflorescence. 3. Acts of God. 4. Improper installation.

**DISCLAIMER AND LIMITATION OF LIABILITY:**

To the best of our knowledge, the information contained herein is accurate. The warranty described herein shall be in lieu of any other warranty, expressed or implied, including but not limited to, any implied warranty of merchantability or fitness for a particular purpose. There are no warranties that extend beyond the description on the face hereof. The Buyer's sole and exclusive remedy against the Seller shall be for the replacement of the products or refund of the purchase price in the event that a defective condition of the products should be found to exist. No other remedy (including, but not limited to, incidental or consequential damages for lost profits, lost sales, injury to person or property, or any other incidental or consequential loss) shall be available to the Buyer. The sole purpose of this exclusive remedy shall be to provide Buyer with replacement of the products or refund of the purchase price of the products if any defect in materials or workmanship is found to exist. The exclusive remedy shall not be deemed to have failed its essential purpose so long as the Seller is willing and able to replace the defective products or refund the purchase price. The Buyer must give the Seller notice in writing of any alleged defect covered by this warranty together with all identifying details, including the Product Code(s), description and date of purchase, within thirty (30) days of the discovery of the defect. Final determination of the suitability of the material for the use contemplated, the manner of use, and whether the use infringes any patents, is the sole responsibility of the Buyer.