

TECH DATA SHEET

(optional – Interiors only)
PROTECTIVE WAX

STEPS for U Do It Coatings' Concrete Stain System:

Degreaser & Stain Treatment (optional - mostly garages)

1 - Eco Prep & Clean (clean/etch concrete)

Patch Kit (optional - to patch concrete)

2 – Decorative Concrete Stain (use one or multiple colors)

Accent Paint (optional – create borders or designs)

3 – Clear Acrylic Sealer (seal concrete)

Protective Wax (suggested to maintain interiors floors)

Maintain Clean (best maintenance cleanser for interiors)

DESCRIPTION AND USE: U Do It Coatings' **Protective Wax** is a non-toxic, non-yellowing acrylic floor finish product for sealed INTERIOR floors. This professional-grade light wax provides a glossy "sacrificial layer," so that the sealer underneath is protected and is less likely to scratch and scuff over time. So, this product not only improves the floor's overall appearance, but helps maintain it.

LIMITATION: For applications that require high-chemical resistance (such as garages, factories or aircraft hangers), **Protective Wax** is NOT recommended for these types of areas, since it can reduce the sealer's chemical-resistance properties. Not recommended for exterior areas.

AVAILABLE IN: One-gallon containers. Larger sizes are not less expensive and are harder to use and ship.

COVERAGE RATE: Approx. 1200 sq. ft. per gallon (one coat). For initial application, 400 sq. ft. (three coats recommended)

SURFACE PREPARATION: Apply to clean, dry, sealed surface. Before applying initial coat of **Protective Wax**, the sealer MUST be fully cured (AT LEAST 72 hours.) If needed, refer to sealer's Tech Data Sheet for more details.

APPLICATION TEMPERATURES: CONCRETE temperature should be between 50-100° F. Do not allow product to freeze during shipping or storage.

INITIAL APPLICATION RECOMMENDATIONS: After sealer has fully cured, clean surface with a neutral cleanser, such as U Do It Coatings' **Maintain Clean** and let dry. Using a spray bottle, mist **Protective Wax** on approximately a 10-sq. ft. area and buff with a microfiber mop until all liquid disappears, leaving a brilliant shine. Work backwards out of the room and repeat this process in sections until entire floor is waxed. Let dry completely (approx. 30 minutes.) Apply a second and third coat (for initial application), letting each dry completely.

MAINTENANCE: Occasional mopping with a neutral cleanser such as U Do It Coatings' **Maintain Clean** will clean and freshen the glossy appearance. Other cleansers can be too harsh and damage the sealer over time. When desired, apply a thin coat of **Protective Wax** after it is clean and dry. This will protect and restore the shine. Stripping is not necessary before reapplication (up to 10 coats.) Eventually, the stained/sealed floor may appear dull/cloudy and stripping is necessary with U Do It Coatings' **Citra-Peel**.

NOTE: If other waxes or polishes were previously used, strip off with U Do It Coatings' **Citra-Peel** before using.

This is an industrial-quality product – USE AT OWN RISK. Follow all directions carefully. Keep out of the reach of children. Read Tech Data Sheet, "Instructions for Staining Interior Concrete Floors," label on container, and SDS (Safety Data Sheet) before using. Watch all How-To Videos on our site and email us at questions@uDoItCoatings.com.

WARNING: Harmful if swallowed. Avoid contact with eyes and skin. Goggles and gloves are recommended. Use with adequate ventilation.

CLEAN UP: Water and mild soap.

DISPOSAL: Dispose of unwanted material per local, state and federal regulations.

HANDLING PRECAUTIONS: Avoid contact with skin. Wear safety glasses and protective gloves. Refer to SDS (Safety Data Sheet) for the most complete information.

FIRST AID: INGESTION: Obtain medical attention at once. EYE CONTACT: Flush with clean water for 15 minutes and obtain medical attention. INHALATION: Remove to fresh air and obtain medical attention. SKIN CONTACT: Wash with soap and water. Obtain medical attention if irritation is severe or persistent. Refer SDS (Safety Data Sheet) for the most complete information.

WARRANTY INFORMATION: If there is a coating failure, such as flaking, peeling, or chipping, it is almost always caused by inferior surface preparation techniques, faulty/inferior concrete, and/or incorrect application technique. If you have reviewed and followed ALL instructional information, contact us to fill out a Complaint Form entirely. Also provide a *U Do It Coatings*’ receipt and ALL batch numbers. We will not accept partially filled out Complaint Forms or for projects over one year old. These Forms will be investigated by *U Do It Coatings* with the cooperation of the contractor/homeowner who installed the products. *U Do It Coatings* will not under any circumstance be liable for damages in excess of the purchase price of the products used on the project. *U Do It Coatings* is not liable for consequential or secondary damages resulting from the failure of a warranted item or the failure to provide services due to conditions beyond its control. **LIMITATIONS ARE DAMAGES CAUSED BY:** 1. The customer due to neglect, abuse, or lack of reasonable care. 2. Settling due to expansive soil, fill dirt movement, drainage, alkali-silica reaction, or efflorescence. 3. Acts of God. 4. Improper installation.

DISCLAIMER AND LIMITATION OF LIABILITY:

To the best of our knowledge, the information contained herein is accurate. The warranty described herein shall be in lieu of any other warranty, expressed or implied, including but not limited to, any implied warranty of merchantability or fitness for a particular purpose. There are no warranties that extend beyond the description on the face hereof. The Buyer’s sole and exclusive remedy against the Seller shall be for the replacement of the products or refund of the purchase price in the event that a defective condition of the products should be found to exist. No other remedy (including, but not limited to, incidental or consequential damages for lost profits, lost sales, injury to person or property, or any other incidental or consequential loss) shall be available to the Buyer. The sole purpose of this exclusive remedy shall be to provide Buyer with replacement of the products or refund of the purchase price of the products if any defect in materials or workmanship is found to exist. The exclusive remedy shall not be deemed to have failed its essential purpose so long as the Seller is willing and able to replace the defective products or refund the purchase price. The Buyer must give the Seller notice in writing of any alleged defect covered by this warranty together with all identifying details, including the Product Code(s), description and date of purchase, within thirty (30) days of the discovery of the defect. Final determination of the suitability of the material for the use contemplated, the manner of use, and whether the use infringes any patents, is the sole responsibility of the Buyer.